





RUGGED TABLET FOR PROFESSIONAL DATA COLLECTION

The LT800H RTK Android tablet is the ultimate solution for an efficient and productive mobile field workforce. With centimeter to decimeter positioning accuracy, this portable, rugged and versatile tablet is perfect for precision GIS data collection, forensic mapping, construction site development, environmental studies or landscaping.

Its 8.1" sunlight-readable display makes it easy to clearly view GIS data tables, complex vector and raster maps, and high-resolution images, even in direct sunlight and high-light areas. Its IP67-rated industrial design enables it to survive daily use in tough environments and conditions, making it a preferred choice for field crew with demanding requirements.

The LT800H brings precision GNSS positioning technology to any organization that needs to collect accurate and reliable data in the field, whether with a single operator or a large field crew.

BRING ACCURACY AT YOUR FINGERTIPS

Leverage the precision of full RTK GNSS

Featuring a high performance 1408 channel GPS, GLONASS, Galileo and BeiDou module and a superior tracking GNSS helix antenna, the LT800H RTK Android tablet delivers best-in-class centimeter to decimeter positioning accuracy in the most challenging environments. Its integrated 4G modem ensures seamless connectivity to GNSS RTK networks corrections

HIGH PERFORMANCE IN ALL ASPECTS

Make data collection seamless

The LT800H RTK Android tablet increases productivity with a built-in 2.0 GHz octa-core processor that displays large maps and data sets without lag or slowdown. Its dual-SIM 4G modem provides fast and reliable connectivity between teams in the field. The sunlight viewable 8.1" Corning Gorilla Glass 3 IPS touchscreen offers extended durability in all environments. In addition, the LT800H capacitive multi-touch screen allows data capture with a stylus, gloves or wet hands to accommodate all working conditions.

HIGH PORTABILITY AND VERSATILE

GMS certified for extended compatibility

The LT800H's Google Mobile Service (GMS) and Android Enterprise Recommended (AER) certifications provide peace of mind in terms of software compatibility and optimal performance. You can be confident that the tablet is designed to work seamlessly with the most popular enterprise data collection applications available in the Google Play Store. The LT800H's certification ensures the highest levels of security and ease-of-use, making it ideal for easy integration into your existing IT ecosystem.

KEEP YOUR DATA SECURE

Industrial IP67 design and 9000mAh Li-ion battery

The LT800H Android RTK tablet is designed to withstand harsh environments and adverse weather conditions, ensuring that your data is always safe, no matter where you collect it. The LT800H also offers an impressive 8 hours of battery life, allowing your mobile workforce to focus on collecting data without interruption. Extended battery life means less downtime and more productive time in the field.





BRING ACCURACY AT YOUR FINGERTIPS

SPECIFICATIONS



S	ystem
Operating system	Android 12.0 GMS certified
CPU	Advanced octa-core CPU 2.0 GHz
RAM	6 GB
ROM	128 GB
Extension	Micro SD card, up to 256 GB
GNSS A	Accuracies (1)
Channel	1408
Constellation	BDS: B1I, B2I, B3I, B1C, B2a, B2b GPS: L1C/A, L1C, L2P (Y), L2C, L5 GLONASS: L1, L2 Galileo: E1, E5a, E5b, E6* QZSS: L1, L2, L5, L6* SBAS*: L1, L5
RTK	2 cm HRMS
SBAS	< 1 m HRMS
D	isplay
Size	8.1" touch screen
Resolution	1920 x 1200
Brightness	600 cd/m ²
Touch screen	Capacitive multi-touch, 5 points
Screen technology	IPS display panel Corning [®] Gorilla [®] Glass 3
Ca	ameras
Front	8 MP
Rear	16 MP
Flash light	Integrated
PI	hysical e
Dust and water proof	IP67 (according to IEC 60529) for water and dust resistance, protected against temporary immersion at a depth of up to 1 m.
Shock	1.2 m fall onto concrete
Humidity	5% - 95% RH (without condensation)
Size (L x W x H)	215.5 mm x 130 mm x 14.5 mm (8.5 in x 5.1 in x 0.6 in)
Weight	570 g (20.1 oz)
Environment	Operating: -20°C to +60°C (-4°F to +140°F) Storage: -40°C to +70°C (-40°F to +158°F)

Communications		
SIM card type	Nano-SIM card	
Wi-Fi	Wi-Fi, IEEE 802.11a/b/g/n/ac	
Bluetooth	Bluetooth™ 5.1	
USB	Type C, OTG	
Network 4G modem	GSM: 850/900/1800/1900 WCDMA: B1/B2/B4/B5/B8/B19 CDMA EVDO: BC0 TD-SCDMA: B34/B39 LTE-FDD: B1/B2/B3/B4/B5/B7/B8/ B12/B17/B18/B19/B20/B26/B28 LTE-TDD: B34/B38/B34/B39/B40/ B41	
Battery		
Li-ion battery capacity	Built-in non-removable battery 9,000 mAh	
Voltage	3.8 V	
Battery life	8 h ⁽²⁾	
Charging time	4.0 h Fast charging: QC 3.0	
Internal sensors		
NFC: G-Sensor: Light Sensor: E-Compass: Gyroscope		

NFC; G-Sensor; Light Sensor; E-Compass; Gyroscope

Accessories

- Screen protector
- Packaging box
- Touch pen
 Type-C USB cable
- Helix antenna
- Charger



1) SBAS and RTK accuracy are based on full GNSS constellations (GPS, Glonass, Galileo and BDS) availability, inder clear unobstructed environment, multipath-free, standard satellite geometry andatmospheric conditions. Performances assume follow up of recommended general GNSS practices. Compliant, but subject to availability of 8DS ICD, Galileo and QZSS commercial service definition, Galileo E6 and QZSS L6 will be provided through future irmware upgrade. (2) 25°C continous data collection in RTK mode, 100% brightness.

©2023 Shanghai Huace Navigation Technology Ltd. All rights reserved. The CHCNAV and CHCNAV logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners. Revision August 2023.

WWW.CHCNAV.COM WWW.ASABA-SURVEYING.ID

PT ASABA Headquarter PT Aneka Sakti Bakti. Jl. Ir. H. Juanda No. 7. Jakarta Pusat 10120.

Phone: (021) 80664499

PT ASABA Branch Office

Bandung Yogyakarta Semarang Surabaya

Medan Balikpapan Pekanbaru Makassar

Banjarmasin Samarinda