

E800

HIGH-PERFORMANCE GNSS RECEIVER

The E800 is a high-performance GNSS receiver that provides an easy-to-use solution for survey professionals who need to collect highly accurate data in a wide range of applications. The durable IP67 design makes it possible to work in extreme environments. The colorful touchscreen is convenient for quick configurations.



GNSS Receiver

5-Watt Internal Radio: Longer Working Distance

No longer need to carry external radio, for its internal radio's working distance can reach 10 - 15 km.

1.45-inch Display: Colorful and Touchable

View the primary status and basic information, set the work mode, and operate the device, facilitating more convenient and direct human-computer interaction.

32GB Internal Memory

The built-in 32GB internal memory can store more data, no need to worry about a long-time span project.

Max 60° Tilt Survey: A Different Way of Working

- Quickly measure accurate points while standing or walking without leveling the pole.
- Concentrate on where the pole tip needs to go, which is especially useful during a stakeout.
- Easily start a survey in environments that are hard to reach, such as building corners and slopes.
- No longer worry about the movement of the pole when measuring, provided that the pole tip is stationary.

Impressive Battery Life: Longer Working Time

Work up to 15 hours and no longer worry about a day's work, with its 13600 mAh battery, which makes your data save safely.

RTK Aid Function: Uninterrupted Work

Work without interruption even when RTK corrections fail, powered by our RTK aid function.



Website



Social media

Product Specification

E800

HIGH-PERFORMANCE GNSS RECEIVER



| GNSS Performance | | |
|----------------------------|--|--------------------------------|
| Satellites tracking | GPS | L1CA, L2P(Y), L2C, L5 |
| | BDS | B1I, B2I, B3I, B1C, B2a, B2b |
| | GLONASS | L1, L2 |
| | GALILEO | E1, E5a, E5b, E6 ¹ |
| | QZSS | L1, L2, L5, L6 ¹ |
| | NavIC | L5 ¹ |
| | SBAS | WAAS, GAGAN, MSAS, EGNOS, SDCM |
| L-Band | B2b PPP (Only for the Asian-Pacific region), HAS ¹ | |
| | | |
| Channels | 1408 | |
| Cold start | < 30 seconds | |
| Warm start | < 20 seconds | |
| Hot start | < 5 seconds | |
| RTK signal initialization | < 5 seconds | |
| Initialization reliability | > 99.9% | |
| Update rate | 20 Hz | |
| High precision static | <ul style="list-style-type: none"> H: 2.5 mm + 0.1 ppm RMS V: 3.5 mm + 0.4 ppm RMS | |
| Static and Fast Static | <ul style="list-style-type: none"> H: 3 mm + 0.5 ppm RMS V: 5 mm + 0.5 ppm RMS | |
| RTK | <ul style="list-style-type: none"> H: 5 mm + 0.5 ppm RMS V: 10 mm + 0.5 ppm RMS | |
| Standard point positioning | <ul style="list-style-type: none"> H: 1.5 m RMS V: 2.5 m RMS | |
| Code differential | <ul style="list-style-type: none"> H: 0.4 m RMS V: 0.8 m RMS | |
| SBAS | <ul style="list-style-type: none"> H: 0.3 m RMS V: 0.6 m RMS | |
| Correction data | RTCM V3.X, RTCM2, CMR | |
| Data output | GGA, ZDA, GSA, GSV, GST, VTG, RMC, GLL, Binary | |

| Power Supply | |
|---------------|--|
| Battery | Rechargeable Built-in Lithium-ion battery x 1 7.2V ~ 13600 mAh |
| Voltage | 9 ~ 28V dc |
| Working time | Up to 15 hours |
| Charging time | Typically 5 hours |

| Internet Modem | |
|----------------|---|
| Support band | Global 4G <ul style="list-style-type: none"> LTE FDD: B1, B2, B3, B4, B5, B7, B8, B12, B13, B18, B19, B20, B25, B26, B28 LTE TDD: B38, B39, B40, B41 UMTS: B1, B2, B4, B5, B6, B8, B19 GSM: B2, B3, B5, B8 |

| System | |
|-------------------|--|
| Operation system | Linux |
| Internal memory | 32 GB |
| Bluetooth | BT 5.0 + EDR, BLE |
| Wi-Fi | 802.11 a/b/g/n/ac |
| SIM card | ✓ |
| TNC | Connect internal radio with antenna |
| 5-pin port | Connect to external radio and external power; NMEA output |
| Type-C port | Charge and data transmission |
| Web UI | View status, update firmware, set up working mode, download data, etc. |
| Intelligent voice | Broadcast working mode and status |
| MEMS | Fast initialization, dynamic tilt survey up to 60° |

| Physical | |
|-----------------------|--|
| Dimension | Φ154 mm x H76 mm |
| Weight | 1500 g |
| Operating temperature | -30°C ~ +65°C |
| Storage temperature | -40°C ~ +80°C |
| Water / dust proof | IP67 |
| Shock | <ul style="list-style-type: none"> Withstand topple over from a 2 m survey pole onto hard surfaces Survive a 1.2 m free drop |
| Vibration | Vibration resistant |
| Humidity | Up to 100% |
| Indicators | Satellites, datalink, battery, Bluetooth |
| Button | Power button, short press to voice broadcast working mode and status |
| Screen | 1.45" colorful touchable screen |
| Certificate | CE, FCC, NGS, IGS |

| Internal Radio | |
|-----------------|---|
| Type | TX and RX |
| Emitting Power | 5 W |
| Operation Range | <ul style="list-style-type: none"> 8 ~ 10 km typically 15km with optimal conditions² |
| Frequency range | 410 ~ 470 MHz |
| Channel spacing | 6.25 KHz ³ / 12.5 KHz / 25 KHz |
| Protocol | Satel, PCC, TrimTalk, TrimMark III, TRANSEOT (PCC-GMSK), South, HiTarget, GEOTALK, GEOMK3, HZSZ |

1: It will be supported through future firmware update.

2: It varies with the obstacle and terrain.

3: It is only available for radio protocol "Satel", and the radio firmware is later than G001.02.27.